RAIL

High performance P-way lubrication

Innovating for tomorrow

TECHNICAL DATA SHEET

Quality Standards:
ISO TS16949: 2009
ISO 9001:2008
ISO 14001: 2004

Issue Date– March 2016

ALL SEASONS P WAY LUBRICANT

Sprayable lubricant for FISHPLATES or POINTS. Can be applied by brush or by using the compression spray unit. All seasons P-Way Lubricant is based on a grease thickener which is well known for its good water resistant characteristics, together with other raw materials to enhance these desirable properties. The main base oil used is solvent refined.

Applications

- For use on fishplates, points and mechanical switch gear
- Apply using a brush or spray
- Suitable hand and eye protection must be worn whilst applying grease

Features and Benefits

- Excellent corrosion protection
- Excellent De-watering
- Protects from oxidation
- Contains extreme pressure additives for high loading requirements
- No run-off after application

Typical Characteristics

Colour	Black
Appearance	Semi-Fluid, Smooth
Thickener Type	Calcium
NLGI Grade	0:0
Penetration	400-430
4 Ball Wear Scar	0.618mm
Temperature Range	>15°C to 30°C
Copper Corrosion (100°C/24h)	1-b

Base Oil Characteristics

Type	Mineral/Solvent
Flash Point (Closed Cup)	>70°C

Pack Size	Network Rail Catalogue Number	LUL Catalogue Number	RS Clare Product Reference Number
12.5kg	0027/004641	17645/425	D0269/00/12.5k

RISQS QUALIFIED

The information contained herein may change. While every care is taken to ensure the accuracy of the material contained in this bulletin, no liability can be assumed for the information given. For specific, current information please contact Clare field sales staff.

RS Clare & Co Ltd
Innovation since 1748